**Edition Date:** 2004-01-19 Revision Date: 2020-02-12

Revised by: Annette Roy, QA Coordinator

Product Name: Histosette® II Catalogue No.: M486-Series

This document replaces any previous version

#### 1. **Product Description:**

**Biopsy Cassette with Separate Lid:** Disposable and non-sterile

- > Available Colors:
  - White, Pink, Green, Yellow, Blue, Peach, Tan, Gray, Lilac, Orange and Aqua
  - Fluorescent Pink, Green and Yellow also available, minimum order quantity required
- 2. Packaging:

Case: 2 boxes of 500 cassettes and 1 box of 1 000 lids / 1 000 units per case

### 3. **Product Specifications:**

Material:

Acetal

➤ Writing surface angle: 45°

> Temperature range: -80°C to +30°C

#### 4. **Standards and Conformity:**

> ISO 2859-1: Sampling and inspection procedures > FDA: Resin conforms to FDA 21 CFR 177.2470 > CONEG / RoHS: Plastics and colorants are in conformity with

CONEG / RoHS standards for heavy metals

> REACH (SVHC): Plastic is in conformity to REACH standards

> LATEX: Material is Latex Free **≻** CE: Product is CE marked

### 5. **Quality Assurance:**

- > Clear, no presence of contamination in plastic
- Visual attributes
- ➤ Lid closure verification

Page 1 / 2 Issue Date: 2017-06-15

Document Template: FRM-106 Rev01 Technical Data Sheet

**Edition Date:** 2004-01-19 **Revision Date:** 2020-02-12

**Revised by:** Annette Roy, QA Coordinator

# 6. Traceability:

**Lot No. Composition:** 8 or 9 digits

### > The lot number can be found in one or all of these locations:

- 1. On exterior case label
- 2. On label inserted inside the master case
- 3. On the inner bag

## 7. Storage Conditions:

- > Store at room temperature in normal warehouse conditions
- > Avoid temperature variations and humidity
- Protect from any possible contamination
- Protect from any damage to the packaging

### 8. Recommended Use:

- Verify proper lid closure of the cassette before using
- > Avoid picric acid, prolonged use in this acid will cause degradation
- > Product is resistant to temperatures of up to 121°C but may release formaldehyde gas when heated
- > Follow chemical resistance chart recommendations
- > For use in automated equipment, follow the equipment manufacturer's instructions

## **OWNERSHIP OF MATERIALS:**

Materials and information contained in this document are **Simport Scientific**'s copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.

Document Template: FRM-106 Rev01 Technical Data Sheet
Page 2 / 2

Issue Date: 2017-06-15