**Edition Date:** 2005-10-08 Revision Date: 2020-05-08

Revised by: Annette Roy, Regulatory

Product Name: Micrewtube® Catalogue No.: T335-6

This document replaces any previous version

1. **Product Description:** 

> > 2 ml Micrewtube<sup>®</sup>: Non-sterile, self-standing tube with Silicone washer seal, flat top

> > screw cap. Caps not assembled.

2. Packaging:

> Case: 1 000 units per case

### 3. **Product Specifications:**

- ➤ Material:
  - Polypropylene tube
  - Polypropylene cap
  - Silicone washer seal
- Certified RNase, DNase, Pyrogen and DNA Free
- > Temperature range: -196°C to +121°C.
- > Autoclavable at 121°C, for up to 30 minutes
- > Centrifuged up to 17 000g

### 4. **Standards and Conformity:**

> ISO 2859-1: Sampling and inspection procedures > FDA: Resin conforms to FDA 21 CFR 177.1520

➤ USP: Resin conforms to USP Class VI

> CONEG: Plastics and colorants are in conformity with

CONEG standards for heavy metals

> REACH (SVHC): Plastic is in conformity to REACH standards

> LATEX: Material is Latex Free ➤ BSE / TSE: Material is BSE / TSE Free

### 5. **Quality Assurance:**

- Clear, no presence of contamination in plastic
- Visual attributes
- Volume measurements
- Closure verification
- Leak proof testing in vacuum at 71.3cm Hg
- Gas phase of Liquid Nitrogen resistance

Page 1 / 2 Issue Date: 2017-06-15

Document Template: FRM-106 Rev01 Technical Data Sheet

**Edition Date:** 2005-10-08 Revision Date: 2020-05-08

Revised by: Annette Roy, Regulatory

### 6. Traceability:

**Lot No. Composition:** 8 or 9 digits

# > The lot number can be found in one or all of these locations:

- 1. On exterior case label
- 2. On label inserted inside the master case
- 3. On the inner bag

### 7. **Storage Conditions:**

- > Store at room temperature in normal warehouse conditions
- Avoid temperature variations and humidity
- Protect from any possible contamination
- Protect from any damage to the packaging

#### 8. **Recommended Use:**

- > Verify proper cap closure when using biohazard material and / or chemical reagents
- > Follow chemical resistance chart recommendations
- > For use in automated equipment, follow the equipment manufacturer's instructions
- Should be used only in the gas phase of Liquid Nitrogen

## **OWNERSHIP OF MATERIALS:**

Materials and information contained in this document are Simport Scientific's copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.

Document Template: FRM-106 Rev01 Technical Data Sheet Page 2 / 2

Issue Date: 2017-06-15