Edition Date: 2004-02-05 Revision Date: 2017-11-03

Revised by: Annette Roy, QA Coordinator

Product Name: Micrewtube® cap Catalogue No.: T340 OSFT

This document replaces any previous version

1. **Product Description:**

Micrewtube® Screw Cap: Disposable, non-sterile flat-top cap with

Silicone washer seal for Micrewtube®.

Tubes sold separately.

> Available colors:

• Natural, Blue, Green, Lilac, Orange, Red, Yellow, White, Brown

> Compatible with:

T341 Micrewtube® Series

2. Packaging:

> Case: 1 000 units per package

3. **Product Specifications:**

Material:

• Cap: Polypropylene • Washer Seal: Silicone

Gamma sterilization resistant;

Temperature range: -196°C to +121°C;

Certified RNase, DNase, Pyrogen and DNA-free;

Autoclavable at 121°C, for up to 30 minutes.

4. **Standards and Conformity:**

> ISO 2859-1: Sampling and inspection procedures > FDA: Resin conforms to FDA 21 CFR 177.1520

> USP: Resin conforms to USP Class VI

➢ CONEG / RoHS: Plastics and colorants are in conformity with

CONEG / RoHS standards for heavy metals

> REACH (SVHC): Plastic is in conformity to REACH standards

Document Template: FRM-106 Rev01 Technical Data Sheet Page 1 / 2

Issue Date: 2017-06-15

Edition Date: 2004-02-05 Revision Date: 2017-11-03

Revised by: Annette Roy, QA Coordinator

5. **Quality Assurance:**

- Clear, no presence of contamination in plastic
- Visual attributes
- Closure verification
- Leak proof testing in vacuum at 71.3cm Hg
- Gas phase of Liquid Nitrogen resistance

6. Traceability:

Lot No. Composition: 8 or 9 digits

> The lot number can be found in one or all of these locations:

- 1. On exterior case label
- 2. On label inserted inside the master case
- 3. On the inner bag

7. **Storage Conditions:**

- > Store at room temperature in normal warehouse conditions
- Avoid temperature variations and humidity
- Protect from any possible contamination
- Protect from any damage to the packaging

8. **Recommended Use:**

- > Verify proper cap closure when using biohazard material and / or chemical reagents
- > Follow chemical resistance chart recommendations
- > For use in automated equipment, follow the equipment manufacturer's instructions
- Should be used only in the gas phase of Liquid Nitrogen

OWNERSHIP OF MATERIALS:

Materials and information contained in this document are Simport Scientific's copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.

Document Template: FRM-106 Rev01 Technical Data Sheet Page 2 / 2

Issue Date: 2017-06-15