Edition Date: 2013-05-28 **Revision Date:** 2018-12-07

Revised by: Annette Roy, QA Coordinator

Product Name: Micrewtube[®] Catalogue No.: T341-4TLST

This document replaces any previous version

1. Product Description:

> 1.5ml Plain Micrewtube*: Non sterile, Low adhesion, self-standing, disposable

tube. Cap sold separately

2. Packaging:

> Case: 1 000 units per package

3. Product Specifications:

Material: Polypropylene with Low Adhesion properties

Certified RNase, DNase, Pyrogen and DNA Free;

> Temperature range: -196°C to +121°C. Autoclavable at 121°C, for up to 30 minutes;

Tubes have plain configuration;

Centrifuged up 17 000 g.

4. Standards and Conformity:

ISO 2859-1: Sampling and inspection procedures
 FDA: Resin conforms to FDA 21 CFR 177.1520

> USP: Resin conforms to USP Class VI

CONEG / RoHS:
Plastics and colorants are in conformity with

CONEG / RoHS standards for heavy metals

REACH (SVHC): Plastic is in conformity to REACH standards

LATEX: Material is Latex FreeBSE / TSE: Material is BSE / TSE Free

5. Quality Assurance:

- Clear, no presence of contamination in plastic;
- Visual attributes;
- Volume measurements;
- Closure verification;
- Leak proof testing in vacuum at 71.3cm Hg;
- Gas phase of Liquid Nitrogen resistance.

Document Template: FRM-106 Rev00 Technical Data Sheet

Issue Date: 2016-04-26

Page 1 / 2

Edition Date: 2013-05-28 **Revision Date:** 2018-12-07

Revised by: Annette Roy, QA Coordinator

Page 2 / 2

6. Traceability:

Lot No. Composition: 8 to 9 digits

➤ The lot number can be found in one or all of these locations:

- 1. On exterior case label;
- 2. On label inserted inside the master case;
- 3. On the inner bag.

7. Storage Conditions:

- Store at room temperature in normal warehouse conditions;
- Avoid temperature variations and humidity;
- Protect from any possible contamination;
- Protect from any damage to the packaging.

8. Recommended Use:

- Verify proper cap closure when using biohazard material and / or chemical reagents;
- > Follow chemical resistance chart recommendations;
- For use in automated equipment, follow the equipment manufacturer's instructions;
- Should be used only in the gas phase of Liquid Nitrogen.

OWNERSHIP OF MATERIALS:

Materials and information contained in this document are **Simport Scientific**'s copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.

Document Template: FRM-106 Rev00 Technical Data Sheet

Issue Date: 2016-04-26