

# Product Name: Septum Screw Caps for Micrewtube<sup>®</sup> Catalogue No.: T347AQX

### This document replaces any previous version

### **1. Product Description:**

> Septum Screw Caps for Micrewtube<sup>®</sup>: Non-sterile, disposable with a pierceable septum

### 2. Packaging:

> Case:

250 units per package

### 3. Product Specifications:

- > Material:
  - Polypropylene cap
  - Silicone and Teflon septum
- > Temperature Range: -80° to 121°C. Autoclavable at 121°C, for up to 30 minutes
- > The Cap incorporates a pierceable septum
- > The septum is pierceable with pipet tip or syringe needle

### 4. Standards and Conformity:

$\triangleright$	ISO 2859-1:	Sampling and inspection procedures
۶	FDA:	Resin conforms to FDA 21 CFR 177.1520
$\triangleright$	CONEG:	Plastics and colorants are in conformity

## with CONEG standards for heavy metals

### 5. Quality Assurance:

- Clear, no presence of contamination in plastic
- Visual attributes
- Dimension measurements
- Closure verification



**Technical Data Sheet** 

Edition Date:2014-12Revision Date:2019-10Revised by:Annetter

2014-12-11 2019-10-23 Annette Roy, QA Coordinator

### 6. Traceability:

- **Lot No. Composition:** 8 to 9 digits
- > The lot number can be found in one or all of these locations:
  - 1. On exterior case label
  - 2. On label inserted inside the master case
  - 3. On the inner bag

### 7. Storage Conditions:

- Store at room temperature in normal warehouse conditions
- > Avoid temperature variations and humidity
- Protect from any possible contamination

### 8. Recommended Use:

- > Verify proper cap closure when using biohazard material and / or chemical reagents
- > Follow chemical resistance chart recommendations

#### **OWNERSHIP OF MATERIALS**:

Materials and information contained in this document are **Simport Scientific**'s copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.