

Edition Date: Revision Date : Revised by:

Product Name: Sample Tube Catalogue No.: T500-4T This document replaces any previous version

1. Product Description:

> 4 ml Sample Tube with Internal Thread:

Non-sterile, disposable, non-printed internal threaded design with round bottom. Caps are sold separately.

> Compatible with:

• T500 Screw Cap Series

2. Packaging:

Case: 1 000 units per package

3. Product Specifications:

- > Material:
 - Polypropylene
- Temperature range: -196°C to +121°C
- Tubes can be autoclaved in upright position with caps loosened at +121°C, for up to 30 minutes
- Gamma radiation resistant
- Centrifuge resistant at up to 17 000 g

4. Standards and Conformity:

ISO 2859-1:	Sampling and inspection procedures
FDA:	Plastic conforms to FDA 21 CFR 177.1520
> USP:	Plastic conforms to USP Class VI
CONEG / RoHS:	Plastic conforms to CONEG / RoHS standards for
	heavy metals
REACH (SVHC):	Plastic is in conformity to REACH standards
LATEX:	Material is Latex Free
BSE / TSE:	Material is BSE / TSE Free

5. Quality Assurance:

- Clear, no presence of contamination in plastic
- Visual attributes
- Dimension and volume measurements
- Closure verification
- Leak proof testing in vacuum at 71.3cm Hg
- Gas phase of Liquid Nitrogen resistance



Edition Date: Revision Date : Revised by: 2004-02-11 2020-08-19 Annette Roy, QA Coordinator

6. Traceability:

- **Lot No. Composition:** 8 or 9 digits
- > The lot number can be found in one or all of these locations:
 - 1. On exterior case label
 - 2. On label inserted inside the master case
 - 3. On the inner bag

7. Storage Conditions:

- > Store at room temperature in normal warehouse conditions
- Avoid temperature variations and humidity
- Protect from any possible contamination
- Protect from any damage to the packaging

8. Recommended Use:

- > Verify proper cap closure when using biohazard material and / or chemical reagents
- > Follow chemical resistance chart recommendations
- > For use in automated equipment, follow the equipment manufacturer's instructions
- > Should be used only in the gas phase of Liquid Nitrogen

OWNERSHIP OF MATERIALS:

Materials and information contained in this document are **Simport Scientific**'s copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.