Edition Date: 2004-01-15 Revision Date: 2017-09-27

Revised by: Annette Roy, QA Coordinator

Product Name: Screw Caps Catalogue No.: T502 Cap Series

This document replaces any previous version

1. **Product Description:**

Screw Caps: Disposable, non-sterile, washer seal cap for external threaded

sample tube

- > Available Colors:
 - Natural, Blue, Dark Green, Gray, Lilac, Orange, Red, White and Yellow
- > Compatible with:
 - T501 Sample Tube Series
 - T312 Capinsert[™] Series
- 2. Packaging:

Case: 1 000 units per package

3. **Product Specifications:**

Material:

> Cap: Polypropylene > Washer: Silicone

> Temperature range: -196°C to +121°C

Autoclavable at 121°C, for up to 30 minutes

> Gamma radiation resistant

4. **Standards and Conformity:**

> ISO 2859-1: Sampling and inspection procedures > FDA: Resin conforms to FDA 21 CFR 177.1520

> USP: Resin conforms to USP Class VI

> CONEG / RoHS: Plastics and colorants are in conformity with

CONEG / RoHS standards for heavy metals

> REACH (SVHC): Plastic is in conformity to REACH standards

> LATEX: Material is Latex Free **▶** BSE / TSE: Material is BSE / TSE Free

Document Template: FRM-106 Rev01 Technical Data Sheet Page 1 / 2

Issue Date: 2017-06-15

Edition Date: 2004-01-15 Revision Date: 2017-09-27

Revised by: Annette Roy, QA Coordinator

Quality Assurance: 5.

- > Clear, no presence of contamination in plastic
- Visual attributes
- > Dimension measurements
- Closure verification
- > Leak proof testing in vacuum at 71.3cm Hg
- > Gas phase of Liquid Nitrogen resistance

6. **Traceability:**

➤ Lot No. Composition: 8 or 9 digits

> The lot number can be found in one or all of these locations:

- 1. On exterior case label
- 2. On label inserted inside the master case
- 3. On the inner bag

7. **Storage Conditions:**

- > Store at room temperature in normal warehouse conditions
- > Avoid temperature variations and humidity
- Protect from any possible contamination
- Protect from any damage to the packaging

8. **Recommended Use:**

- > Verify proper cap closure when using biohazard material and / or chemical reagents
- > Follow chemical resistance chart recommendations
- > For use in automated equipment, follow the equipment manufacturer's instructions
- Should be used only in the gas phase of Liquid Nitrogen

OWNERSHIP OF MATERIALS:

Materials and information contained in this document are **Simport Scientific**'s copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.

Document Template: FRM-106 Rev01 Technical Data Sheet Page 2 / 2

Issue Date: 2017-06-15