**Edition Date:** 2008-12-08 **Revision Date:** 2021-03-16

**Revised by:** Annette Roy, Regulatory

Product Name: Cryovial® Catalogue No.: T309-4A

This document replaces any previous version

# 1. Product Description:

➤ 4 ml Cryogenic Vial with Cap: Sterile, disposable, self-standing, external threaded design

assembled with lip-seal cap.

2. Packaging:

Case: 10 bags of 100 units / 1 000 units per case

## 3. Product Specifications:

Material:

Tube: PolypropyleneCap: Polypropylene

- RNase, DNase, Pyrogen and DNA Free
- ➤ Gamma radiation sterilized at a SAL of 10<sup>-3</sup>; specified dose between 6.5 kGy and 13.5 kGy
- > Temperature range: -196°C to +121°C. Autoclavable at 121°C for up to 30 minutes
- > Tubes have printed graduations and writing area
- ➤ Insertion of a Capinsert<sup>TM</sup> (T312 Series) allows for color coding identification

## 4. Standards and Conformity:

ISO 2859-1: Sampling and inspection procedures
 FDA: Resin conforms to FDA 21 CFR 177.1520

> USP: Resin conforms to USP Class VI

CONEG / RoHS:
Plastics and colorants are in conformity with

 ${\tt CONEG/RoHS\ standards\ for\ heavy\ metals}$ 

> REACH (SVHC): Plastic is in conformity to REACH standards

LATEX: Material is Latex Free
 BSE / TSE: Material is BSE / TSE Free
 CE: Product is CE marked

Document Template: FRM-106 Rev01 Technical Data Sheet

Issue Date: 2017-06-15

**Edition Date:** 2008-12-08 **Revision Date:** 2021-03-16

**Revised by:** Annette Roy, Regulatory

## 5. Quality Assurance:

- Clear, no presence of contamination in plastic
- Visual attributes
- Volume measurements
- Closure verification
- Leak proof testing in vacuum at 71.3cm Hg
- Gas phase of Liquid Nitrogen resistance.

### 6. Traceability:

**Lot No. Composition:** 8 or 9 digits

#### > The lot number can be found in one or all of these locations:

- 1. On exterior case label
- 2. On label inserted inside the master case
- 3. On the inner bag

### 7. Storage Conditions:

- Store at room temperature in normal warehouse conditions
- Avoid temperature variations and humidity
- Protect from any possible contamination
- Protect from any damage to the packaging, which could compromise the product sterility

#### 8. Recommended Use:

- Verify proper cap closure when using biohazard material and / or chemical reagents
- > Follow chemical resistance chart recommendations
- For use in automated equipment, follow the equipment manufacturer's instructions
- > Should be used only in the gas phase of Liquid Nitrogen

#### **OWNERSHIP OF MATERIALS:**

Materials and information contained in this document are **Simport Scientific**'s copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.

Document Template: FRM-106 Rev01 Technical Data Sheet
Page 2 / 2

Issue Date: 2017-06-15