

Edition Date: Revision Date : Revised by:

# Product Name: Micrewtube<sup>®</sup> Catalogue No.: T332-6

This document replaces any previous version

- 1. Product Description:
  - 2 ml Micrewtube<sup>®</sup>: Non-Sterile, self-standing tube with Silicone washer seal screw cap and attachment loop. Caps are pre-attached and not screwed on.
- 2. Packaging:
  - Case: 10 bags of 50 for a total of 500 units per case
- 3. Product Specifications:
  - > Material:
    - Polypropylene tube
    - Polypropylene cap
    - Silicone washer seal
  - Certified RNase, DNase, Pyrogen and DNA Free
  - Temperature range: -196°C to +121°C.
  - Autoclavable at 121°C, for up to 30 minutes
  - Centrifuged up to 17 000g

## 4. Standards and Conformity:

- ISO 2859-1: Sampling and inspection procedures
- FDA: Resin conforms to FDA 21 CFR 177.1520
- USP: Resin conforms to USP Class VI
- CONEG: Plastics and colorants are in conformity with
- CONEG standards for heavy metals
- REACH (SVHC): Plastic is in conformity to REACH standards
- LATEX: Material is Latex Free
- BSE / TSE:Material is BSE / TSE Free

## 5. Quality Assurance:

- Clear, no presence of contamination in plastic
- Visual attributes
- Volume measurements
- Closure verification
- Leak proof testing in vacuum at 71.3cm Hg
- Gas phase of Liquid Nitrogen resistance



Edition Date: Revision Date : Revised by: 2005-10-08 2020-05-06 Annette Roy, Regulatory

## 6. Traceability:

- **Lot No. Composition:** 8 or 9 digits
- > The lot number can be found in one or all of these locations:
  - 1. On exterior case label
  - 2. On label inserted inside the master case
  - 3. On the inner bag

## 7. Storage Conditions:

- Store at room temperature in normal warehouse conditions
- > Avoid temperature variations and humidity
- Protect from any possible contamination
- Protect from any damage to the packaging

## 8. Recommended Use:

- > Verify proper cap closure when using biohazard material and / or chemical reagents
- > Follow chemical resistance chart recommendations
- > For use in automated equipment, follow the equipment manufacturer's instructions
- Should be used only in the gas phase of Liquid Nitrogen

## **OWNERSHIP OF MATERIALS**:

Materials and information contained in this document are **Simport Scientific**'s copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.